| PrintStik PS910 Specifications | | |
|---|---|---|
| Part Number | DPEN-PS910 | |
| UPC Code | 8395340091002 | |
| Unit Size/Weight | 2.5 cm x 4.8 cm x 27.9 cm (1” x 1.9” x 11”), .5 kg (1.1 lbs) w/cartridge installed. | |
| Retail pack/Weight | 15.2 cm x 33 cm x 6.4 cm (6” x 13” x 2.5”), 1.4 kg (3 lbs) | |
| Master Carton/Weight | 38.1 cm x 43.2 cm x 33 cm (15” x 17” x 13”), 9.1 kg (20 lbs) | |
| Resolution | Approx 200x100 dpi, 200x200 dpi, 200x400 dpi | |
| Method | Direct Thermal Printing | |
| Speed | Up to three pages per minute | |
| Paper sizes (Roll) | Paper Cartridge 21.5 cm (8.5") wide, 20 pages | |
| Interface | Wireless Bluetooth + Standard USB 2.0 | |
| Power supply Options | AC - 100-240 VAC, 50 or 60 Hz with AC Adapter | DC – 12/24V VDC from standard Automobile cigarette lighter socket |
| Number of pages per charge | Up to 30 pages | |
| Battery type | Printstik Rechargeable Lithium-ion Polymer | |
| Regulatory | CE, IC, FCC | |
| Operating System Supported | Microsoft Windows 98/2000/ME/XP/Vista<br>Blackberry and other Java phones<br>(Check Website for new additions) | |

Printstik Contents:

PS910 PRINTSTIK printer
Nylon zipper case
Wall Charger
Auto Charger
Paper cartridge
Quick Start Guide
Installation CD with User Manual